


- |                       |   |
|-----------------------|---|
| (1) BLINDING CONCRETE | (7) PERFORATED PIPE                       |
| (2) FOOTING           | (8) GRAVEL                                |
| (3) RETAINING WALL    | (9) "FILTONIL" FILTER FABRIC<br>200 GM/M2 |
| (4) MBM WATERPROOFING |   |
| (5) PROTECTION BOARD  |   |
| (6) BACK FILL         |   |

**NOTES :**

- 1- ALL EXTERNAL ANGLES OF FOUNDATIONS ARE PROVIDED WITH 20X20 MM CHAMFER.  
 2- ALL INTERNAL ANGLES ARE PROVIDED WITH 40X40 MM CANT STRIP.  
 3- OTHER FOOTING SURFACES IN DIRECT CONTACT WITH EARTH SHALL BE PROTECTED WITH LIQUID APPLIED BITUMINOUS COATING

( USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION )

	Application	<b>WATERPROOFING APPLICATIONS</b>	<b>UR10</b>
		<b>FOUNDATIONS</b>	
		<b>RETAINING WALLS</b>	
Conditions	AT EARTH DIFFERENT LEVELS, IN LANDSCAPING AND ROADS APPLICATIONS		REFERENCE:
System	MBM MEMBRANE SYSTEM, DRAINAGE SYSTEM OPTIONAL		BNTS/03/UR10
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	DATE:
TEL : 202 451 1104 - 202 451 1105 FAX: 202 451 1108		Web Site: www.bitunil.com	NOVEMBER 2014