



- (1) CONCRETE DECK
- (2) SLOPED CONCRETE
- (3A) MBM WATERPROOFING BASE LAYER
- (3B) MBM SELF PROTECTED WATERPROOFING MAIN LAYER
- (4) 50X50 MM MORTAR CANT STRIP
- (5) "BITUFLASH-FM" BASE FLASHING
- (6) COUNTER FLASHING SYSTEM, ALUMINIUM & SEALANT

**NOTES :**

- 1- BASE LAYER CAN BE APPLIED SEMI-BONDED, WHILE MAIN LAYER MUST BE FULLY BONDED ONTO THE BASE LAYER.
- 2- FOR LIGHT TRAFFIC SERVICEABLE ROOFS, WALKWAYS CAN BE CREATED WITH A MINERAL FINISHED MEMBRANE OF A DIFFERENT FINISH COLOUR THAN THE ROOF.
- 3- THIS SYSTEM IS IDEAL FOR FUTURE MAINTENANCE WORKS

( USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION )

	<b>Application</b>	<b>ROOFING APPLICATIONS</b>	<b>RC31</b>
	<b>Deck Type</b>	<b>CONCRETE DECK - FLAT ROOFS</b>	
	<b>Use</b>	<b>NON-ACCESSIBLE</b>	
	<b>Finish</b>	EXPOSED (MBM SELF-PROTECTED MEMBRANE)	REFERENCE:
	<b>Assembly</b>	NON-INSULATED	BNTS/03/RC31
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt. TEL 202 451 1104 - 202 451 1105 FAX 202 451 1108		E-mail: bitunil@bitunil.com Web Site: www.bitunil.com	<b>DATE:</b> <b>NOVEMBER 201</b>