


- | | |
|----------------------------|--|
| (1) CONCRETE BRIDGE DECK | (4) "BITUFLASH-RS 200" REINFORCING STRIP |
| (2) MBM WATERPROOFING | (5) MBM BASE FLASHING |
| (3) ASPHALT WEARING COARSE | (6) PROTECTION LAYER |

NOTES :

- 1- BRIDGE DECK JOINTS MUST BE FILLED UP (GROUTED) AND COVERED WITH 200 MM MBM REINFORCING STRIP PRIOR TO MEMBRANE APPLICATION.
- 2- MEMBRANE SHALL BE FULLY BONDED TO BRIDGE DECK.
- 3- MEMBRANE SHALL BE APPLIED PARALLEL TO TRAFFIC DIRECTION, STARTING DOWN HILL AND UPWARDS.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	CIVIL ENGINEERING APPLICATIONS	CB10
		BRIDGE DECK	
	Conditions	COVERED WITH ASPHALT WEARING COARSE	
System	MBM WATERPROOFING BRIDGE DECK SYSTEM	REFERENCE: BNTS/03/CB10	
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt. TEL: 202 451 1104 - 202 451 1105 FAX: 202 451 1108		E-mail: bitunil@bitunil.com Web Site: www.bitunil.com	DATE: NOVEMBER 2014