


- |   |   |
|---|---|
| (1) BRICK OR CONCRETE WALLS               | (3) HEAT INSULATION MECHANICALLY FASTENED |
| (2) MBM SELF-ADHESIVE DAMP PROOFING LAYER | (4) MARBLE CLADDING MECHANICALLY FIXED    |

**NOTES :**

- 1- SURFACE OF ELEVATION SHALL BE CLEAN, DRY, SMOOTH, AND PRIMED WITH A COAT OF "PRIMANIL- 41" .  
 2- LIQUID APPLIED DAMP PROOFING MEMBRANE CAN BE SPECIFIED BY THE DESIGNER.

( USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION )

	Application	<b>MISCELLANEOUS APPLICATIONS</b>	<b>MF10</b>
		<b>FACADES DAMP-PROOFING</b>	
	Conditions	CLADDED FACADES, MECHANICALLY FIXEC CLADDING	
System	MBM SELF-ADHESIVE MEMBRANE SYSTEM	REFERENCE: BNTS/03/MF10	
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt. TEL : 202 451 1104 - 202 451 1105 FAX: 202 451 1108		E-mail: bitunil@bitunil.com Web Site: www.bitunil.com	DATE: NOVEMBER 2014