

- (II) PILE
- (12) DRAINAGE PIPE
- (13) DRAINAGE BOARD
- (14A) MBM VERTICAL WATERPROOFING, BASE LAYER "NILOFLEX 15 3MM E/E" \*
- (14B) MBM VERTICAL WATERPROOFING, MAIN LAYER "NILOSTICK | 500-3 MM S/Z"
- (15) FORE PILE (DOWELLS)
- (16) BACK FILL

## (8) RC RAFT FOUNDATION

(9)RC RAFT RETAINING WALL

## NOTES:

- 1- THE DRAINAGE IS PLACED AS A SURROUNDING BELT ALONG THE CONTINUOUS FOUNDATION AS PER PROJECT REQUIREMENTS.
- 2- FLASHING:
  - OPTION A CAST-IN PLACE POLYURETHANE COATING REINFORCED WITH POLYESTER.

WATERPROOFING, BASE LAYER

WATERPROOFING, MAIN LAYER

"NILOFLEX 15 3MM E/E"

"NILOFLEX 15 4MM E/E"

(4B) MBM HORIZONTAL

(5) PROTECTION BOARD\*

(7) IRON REINFORCEMENT

(6) WATER SWELL TAPE

- OPTION B ADDITIONAL STRIP OF NILOFLEX 15 PY S/E.
- OPTION C AS SPECIFIED.
- \* OPTIONAL IN CASE OF EXPECTED MECHANICAL MOVEMENT PROTECTION BOARD IS REQUIRED (NILOBOARD, NILOSTICK 1500 2MM S/E OR ALTERNATE).
- MECHANICALLY FASTENED TO DRAINAGE BOARD.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

