


- (1) CONCRETE DECK
- (2) SLOPED CONCRETE
- (3) MBM WATERPROOFING
- (4) "SEPANIL" SEPARATION LAYER 150 MICRONS
- (5) XPS INSULATION ,50MM
- (6) FILTER FABRIC, 100-120 GM/M2
- (7) SAND & MORTAR BED
- (8) TILES, AS SPECIFIED
- (9) 50X50MM MORTAR CANT STRIP
- (10) "BITUFLASH-FM" BASE FLASHING
- (11) 20X20MM GROOVE, POINTED WITH BITUMEN MASTIC
- (12) TILTED TILE

NOTES :

1- MEMBRANE BASE FLASHING TERMINATION SHALL BE MIN. 100 MM ABOVE ROOF FINISH LEVEL.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	ROOFING APPLICATIONS	RC10
	Deck Type	CONCRETE DECK - FLAT ROOFS	
	Use	ACCESSIBLE	
	Finish	PROTECTED WITH TILES , MARBLE OR AS SPECIFIED	REFERENCE:
	Assembly	INVERTED ROOF MEMBRANE ASSEMBLY (IRMA)	BNTS/03/RC10
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	DATE:
TEL: 202 451 1194 - 202 451 1195		FAX: 202 451 1198	NOVEMBER 2014
		Web Site: www.bitunil.com	