



- | | |
|-----------------------------------|---|
| (1) CONCRETE DECK | (7) 50X50 MM MORTAR CANT STRIP |
| (2) SLOPED CONCRETE | (8) "BITUFLASH-FM" BASE FLASHING |
| (3) MBM WATERPROOFING | (9) 20X20 MM GROOVE, POINTED
WITH BITUMEN MASTIC |
| (4) SEPARATION LAYER
200 GM/M2 | (10) TILTED TILE |
| (5) SAND & MORTAR BED | |
| (6) TILES, AS SPECIFIED | |

NOTES :

1- MEMBRANE BASE FLASHING TERMINATION SHALL BE MIN. 100 MM ABOVE ROOF FINISH LEVEL.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	ROOFING APPLICATIONS	RC12
	Deck Type	CONCRETE DECK - FLAT ROOFS	
	Use	ACCESSIBLE	
	Finish	PROTECTED WITH TILES , MARBLE OR AS SPECIFIED	REFERENCE:
	Assembly	NON INSULATED	BNTS/03/RC12
50, Al Khalifa Al Maamoun St., Roxy, Heliopolis, Cairo - Egypt.		E-mail: bitunil@bitunil.com	DATE:
TEL 202 451 1104 - 202 451 1105 FAX 202 451 1108		Web Site: www.bitunil.com	NOVEMBER 2014