



- | | |
|------------------------------------|-----------------------|
| (1) BLINDING CONCRETE | (4) BACK FILL |
| (2) FOOTING | (5) BLINDING CONCRETE |
| (3) LIQUID APPLIED BITUMEN COATING | (6) MBM DAMP PROOFING |
| | (7) SLAB ON GRADE |

NOTES :

- LIQUID BITUMINOUS PROTECTION SHALL BE IN TWO COATS APPLIED IN RIGHT DIRECTIONS TO GUARANTEE FULL COVERAGE OF CONCRETE SURFACE.
- EXTERNAL PERIMETER WALLS SHALL BE PROTECTED WITH THE BITUMINOUS COATING UP TO 400 MM ABOVE THE ZERO LEVEL, SPECIALLY WHEN EXPOSED TO RAIN OR SPLASHING WATER.
- MEMBRANE PROTECTING SLAB ON GRADE SHALL BE TERMINATED HORIZONTALLY COVERING THE GRADE BEAM TOP TO CREATE A CONTINUOUS BARRIER.

(USE "SYSTEM REFERENCE" TO OBTAIN RELEVANT DETAILS FROM "STANDARD CONSTRUCTION DETAILS" SECTION)

	Application	WATERPROOFING APPLICATIONS	UF10
		FOUNDATIONS	
		FOOTING & SLABS-ON-GRADE	
	Conditions	AT GROUND LEVEL, DRY OR DAMP SITES	REFERENCE: BNTS/03/UF10
System	LIQUID APPLIED BITUMEN ON FOOTINGS	DATE: NOVEMBER 2014	
	50, Al Khalifa Al Maamoun St., Roxy, Heliopolis - Cairo - Egypt. TEL : 202 451 1194 - 202 451 1195 FAX: 202 451 1198	E-mail: bitunil@bitunil.com Web Site: www.bitunil.com	